

## EMF DATASHEET FOR ARC WELDING POWER SOURCE

### EQUIPMENT INFORMATION

Manufacturer: Fronius  
 Model: TransSteel 3500 Rob; TransSteel 3500 MV Rob nc; TransSteel 3500 Rob nc; TransSteel 3500 Rob nc;  
 TransSteel 3500 MV Rob nc  
 Model Number: 4,075,163; 4,075,163,630; 4,075,163,639; 4,075,163,800; 4,075,163,830  
 Intended use: ☒ occupational ☐ by laymen

### BASIC INFORMATION

Applied Regulations: Directive 2014/35/EU  
 Referenced Limits: Directive 2013/35/EU, Recommendation 1999/519/EC  
 Applied Standards: EN 62822-1:2016, EN 62822-2:2016

Non-thermal effects need to be considered for the workplace assessment ☒ yes ☐ no  
 Thermal effects need to be considered for the workplace assessment ☐ yes ☒ no

- ☒ Data based on maximum power source capability  
☐ Data based on worst case setting/program  
☐ Data based on multiple settings / programs

### COMPLIANCE SUMMARY

Compliance with ELVs for health effects at standardized configurations ☒ yes ☐ no  
 Compliance with ELVs for sensory effects at standardized configurations ☒ yes ☐ no  
 All values below the Action Levels at the standardized configurations ☐ yes ☒ no

### NON-THERMAL EFFECTS

	HEAD		TRUNK	LIMB HAND	LIMB THIGH
	SENSORY EFFECTS	HEALTH EFFECTS			
Standardized distance	10.00 cm	10.00 cm	10.00 cm	3.00 cm	3.00 cm
EI at standardized distance	0.30	0.29	0.47	0.26	0.60
Required minimum distance	2.00 cm	1.00 cm	3.00 cm	1.00 cm	1.00 cm

Distance where all EIs fall below 20: % 35.00 cm  
 Distance where compliance with general public limits is reached: 3.00 m